

INDIAN INSTITUTE OF SCIENCE EDUCATION AND RESEARCH THIRUVANANTHAPURAM (IISERTVM) (Govt. of India, Ministry of H.R.D)

CET CAMPUS, KULATHUR, ENGINEERING COLLEGE.P.O THIRUVANANTHAPURAM 695016, KERALA, INDIA.

Рн: 0471-2597454 Fax:0471-2597427

EMAIL: PURCHASESTORES@IISERTVM.AC.IN

Date: 27th November 2015

INVITATION TO TENDER(IND)

No: IISER/PUR/6604/15

Due Date: 15th December 2015 [4PM]

Date of Opening: 16th December 2015 [3PM]

Dear Sirs,

SUB: Supply of Programmable Spin Coating System.

We invite Sealed Tenders for the following items:

S1 #:	Item/ Description	Qty	
1.	Programmable Spin Coating System	1 No.	
	Specification as per annexure I		
Please quote your lowest rate and shortest delivery period as per the following terms. Your offer			
in sealed cover Superscribing Tender Number and Due Date shall reach us on or before the			
due date and time. Please follow "Instruction to Tenderers" attached.			
		_	

EMD

: Rs. 11,600/-in the form of DD or B.G. to be submitted along with the quote. Quote received without EMD will be summarily rejected.

Payment

: Within 30 days after supply and installation/Net 30 days /LC. No

advance payment will be made by IISERTVM.

Delivery

: To be delivered at our stores (Free delivery). If import, mention

Ex-works/FCA/CIP terms with clear breakup charges.

Taxes & Duties

: Indicate taxes and duties. We are exempted for customs duty under 51/96 notification and Excise duty under 10/97

Discount

notifications.
: Indicate, if any.

Delivery Schedule

: Required Immediately. Indicate your schedule

Validity of quote

: 60 days

Thanking You,

Yours Faithfully

(K.Bhaskara Rao) Deputy Registrar Purchase & Stores

P.S. CATALOGUE/LEAFLET FEATURING ALL TECHNICAL SPECS/INFORMATION OF THE PRODUCT QUOTED SHALL ACCOMPANY THE OFFER.

Specifications

Model type	Programmable
Rotational Speed	0 to 9999 RPM or higher in 1 RPM increments
Acceleration / deceleration time	At least 0.1 to 30 sec in 0.1 sec increments
Dwell time	At least 0 to 999 sec in 1 sec increments
Dispense time	At least 10 to 30 sec in 0.1 sec increments
Bowl size	8 inch
Vacuum chuck 1	O-ring vacuum holding, 0.25 inch
Vacuum chuck 2	O-ring vacuum holding, 0.50 inch
Vacuum input minimum	At least 430 mm Hg with O.D. fitting 6.35 mm
Purge input	At least 0.55 CFM at 5 psi of dry air or N ₂
Vacuum pump	Oil free, 1/3 HP, 5.1CFM 27" HG Max Vacuum
£	220V/50Hz
Power input	220V/50Hz

[Deputy Registrar] Purchase & Stores